

The dimensions and clearances on this page are for reference only!  Refer to the Owner's Manual prior to installation. We recommend all Fireplace Xtrordinair® appliances be installed, and maintained on an annual basis by your Specialty Hearth Retailer.	B & B - Intimate		564 Collection - Bedrooms & Family Rooms		
	Bed & Breakfast TRV Deluxe	564 TRV 25K Deluxe	564 TRV 25K Clean Face Deluxe	564 TV High Output Deluxe	
<b>Features &amp; Options You're Gonna Love</b>					
GreenSmart® Basic or Deluxe	Deluxe	Deluxe	Deluxe	Deluxe	
Dancing-Fyre™ Burner	N/A	YES	YES	YES	
Ember-Fyre® Burner	YES	N/A	N/A	YES	
Diamond-Fyre™ Burner	N/A	N/A	N/A	YES	
Comfort Control™	YES	YES	YES	YES	
Convection Fan	90 CFM	180 CFM	180 CFM	180 CFM	
Accent Lights	REAR	OVERHEAD	OVERHEAD	REAR, OVERHEAD Dancing-Fyre™ & Ember-Fyre® BOTTOM, OVERHEAD Diamond-Fyre™	
Ember-Glo™	N/A	YES	YES	N/A	
Cool Smart TV Wall™ Option	N/A	YES	YES	N/A	
Power Exhaust Vent Option	N/A	YES	YES	YES	
Power Heat Duct Option	N/A	N/A	N/A	ONE	
<b>Specifications</b> Gas appliance performance can be affected by negative pressure in the home and by prevailing atmospheric conditions. Efficiency may vary depending on vent configuration and atmospheric conditions. Contact local building or fire officials about restrictions and installation requirements in your area.					
Height (including standoffs)	34-1/8"	37"	37"	36-1/4"	
Width	20-1/8" Front	37-1/4"	38-1/4"	36-1/4"	
Depth	13 5/8" TV 12 3/8" RV	17-1/4"	19-1/8"	18-1/4"	
Flue Diameter May be reduced. Ask your dealer.	8"	8"	8"	8"	
Direct Vent Top Vent	YES	YES	YES	YES	
Direct Vent Rear Vent	YES	YES	YES	N/A	
Weight	95 lbs.	155 lbs.	155 lbs.	165 lbs.	
Glass Size	397 sq. in.	564 sq. in.	564 sq. in.	564 sq. in.	
Combustible Min. Mantel Clearances (Measured from base of fireplace to mantle)	Determined by face 4" to 9" above face	35-3/4" - 38-1/2"	35-3/4" - 38-1/2"	40-3/4" - 48-1/2"	
Custom Shop Cast Mantel Clearances	N/A	See your Authorized Fireplace Xtrordinair® dealer for details.			
Hearth Requirement	None	None	None	None	
<b>Performance</b>					
Heating Capacity (Up To)	650 Sq. Ft.	1,250 Sq. Ft.	1,250 Sq. Ft.	1,700 Sq. Ft.	
BTU Input High to Low (NG)	16,500 - 6,000	25,000 - 7,500	25,000 - 7,500	35,000 - 10,400	
BTU Input High to Low (LP)	16,500 - 5,000	25,000 - 6,500	25,000 - 6,500	35,000 - 7,500	
Turndown Ratio	64% NG 70% LP	70% NG 74% LP	70% NG 74% LP	71% NG 79% LP	
Canadian EnerGuide P4 Efficiency	67.62% NG 71.28% LP	70.28% NG 71.10% LP	70.28% NG 71.10% LP	64.64% NG 66.08% LP	
Steady State Efficiency High (Up to)	77.94% NG 81.71% LP	79.67% NG 80.16% LP	79.67% NG 80.16% LP	78.10% NG 79.69% LP	
AFUE (Annual Fuel Utilization Efficiency)	72.50% NG 72.70% LP	68.10% NG 72.10% LP	68.10% NG 72.10% LP	67.20% NG 65.70% LP	
<b>40</b> NOTE: Improper installation of your gas appliance or failure to operate it in accordance to the guidelines detailed in the Owner's Manual may negate your warranty and endanger your home and family. Installation information is available on our website at <a href="http://www.fireplacex.com">www.fireplacex.com</a> .					